INDOOR LUMINAIRES — TRACK LIGHT

VUE-3 DIP Track Light

24W / 30W / 40W | DIP POWER + CCT | 3-WIRE SINGLE-CIRCUIT | NON-DIM

220–240V · 3-WIRE SINGLE-CIRCUIT ADAPTER · WHITE / BLACK / GREY · 5-YEAR WARRANTY




KEY FACTS

VUE-3 is a 3-wire DIP-selectable track light that presets both power and CCT inside one single-circuit adapter for 220–240V rails. One SKU covers nine combos — 24W (400/500/600mA), 30W (550/650/750mA), 40W (850/950/1050mA) with warm/neutral/cool DIP — flicker-free, PF >0.9, on/off only.

POWER	24W / 30W / 40W — DIP 400–1050mA
LIGHT	Warm / Neutral / Cool (DIP dial) · Non-dim
CCT	Warm / Neutral / Cool (DIP preset)
SUPPLY	220–240V · 3-wire single-circuit
ADAPTER	172*32*47MM · PF >0.9 · flicker-free
FINISH	White Black Grey

Supermarkets · Boutiques · Chain stores · Grocery aisles

ORDERING — VUE-3 · 24W / 30W / 40W



ORDER CODE	POWER	ADAPTER	CCT
5414024S	24W	172*32*47MM	Warm / Neutral / Cool
5414030S	30W	172*32*47MM	Warm / Neutral / Cool
5414040S	40W	172*32*47MM	Warm / Neutral / Cool

※ Full code = table code + FIN(B/W/G) + CCT(K30/K40/K50), e.g. 5414024SB-K40 DIM S built in (DIP preset only)
N=Non-dim · P=TRIAC · V=0-10V · D=DALI · C=Casambi BLE · R=Knob · S=DIP preset
Tracks 3/4/6-wire on request — contact sales for more.



APPLICATION

- **One SKU, nine combos:** preset power (24/30/40W) and tone (warm/neutral/cool) by two DIP banks before first switch-on — no rewiring, no app.
- **Single-circuit refits:** clicks onto 220–240V 3-wire rails (GLOBAL / POWERGEAR equivalents) in white, black or grey to match the existing track.
- **Merchandise rule:** warm for bakeries/wood, neutral for apparel, cool for supermarkets and drinks — set per zone, not per carton.
- **Stock rule:** distributors hold three VUE-3 heads instead of nine fixed-output SKUs; settings never drift in staff hands.

CCT LUMEN MULTIPLIER — RATED @4000K

CCT	MULTIPLIER	EXAMPLE (40W)
3000K	×0.95	5510lm
4000K	×1.00 (rated)	5800lm
5000K	×1.03	5974lm

Example @40W estimated at 145 lm/W pending LM-79. Multipliers are the factory standard for this series; re-validate by LM-79 per CCT when available.

NOTES

- **Ordering:** White / Black / Grey finish — add FIN B/W/G; CCT chosen by DIP banks at install (warm/neutral/cool, 3000/4000/5000K). Confirm Kelvin per position before shipment; decide FIN + CCT suffix together (e.g. SB-K40).
- **Supply & control:** 220–240V AC 50/60Hz · 3-wire single-circuit adapter 172*32*47mm · Non-dim on/off only, PF >0.9, flicker-free; DIP S preset locked, not live-dimmable.
- **Rail compatibility:** Fits 3-wire single-circuit profiles (GLOBAL, POWERGEAR and equivalents); does not fit 3-phase, 6-wire DALI, 48V magnetic or 120V tracks — send a rail-end photo for adapter keying check.
- **Warranty & family:** 5-year warranty with spare DIP 2-in-1 adapters; for 3-phase multi-circuit buildings see VUE-D 650 DIP, for knob live-dim see VUE-K, for wall-dimmer see VUE-T.

Scan for live datasheet