OUTDOOR LUMINAIRES — BOLLARD

CORN-H Aluminum LED Path Bollard

CORN-H 12W · 170x120 compact head | SMD | 2700K / 4000K | Ra80

HEIGHTS 300 / 400 / 600 / 800 / 1000 MM · DIE-CAST AL + PC · 100–240V




KEY FACTS

CORN-H is an aluminum path bollard that lights the walkway edge, not the facade. One 12W SMD engine in a compact 170x120mm head serves five heights from 30 to 100cm — short heads edge flower beds, tall heads carry main walkways — at 2700K/4000K Ra80.

POWER	12W · SMD
HEIGHTS	300–1000 mm · 5 models
LIGHT	SMD · 2700K/4000K · Ra80
BODY	AL + PC · 100–240V · Non-dim
FINISH	Sand Black Sand Gray

Villas · Walkways · Courtyards · Gardens · Driveways

ORDERING — CORN-H COMPACT-HEAD · 12W



PRODUCT	DIMENSION	CRI	CCT	POWER
411730 12K3/K4	170*120*300MM	Ra80	2700K/4000K	12W
411740 12K3/K4	170*120*400MM	Ra80	2700K/4000K	12W
411760 12K3/K4	170*120*600MM	Ra80	2700K/4000K	12W
411780 12K3/K4	170*120*800MM	Ra80	2700K/4000K	12W
4117100 12K3/K4	170*120*1000MM	Ra80	2700K/4000K	12W



APPLICATION

- **Height rule:** 30–40 cm heads edge flower beds and low planting · 60–100 cm heads carry main walkways, gates and driveways.
- **Spacing rule:** 2.5–4 m apart so the pools just overlap — stagger the two sides and tighten at steps, curves and gates.
- **CCT rule:** 2700K beside terraces, planting beds and seating · 4000K for driveways and side passages where neutral white reads safer.
- **Setting rule:** compact villa head for private walkways and courtyards · square park columns see CUBO-G · slim architectural accent see LAN.

NOTES

- **Ordering suffix:** K3 = 2700K · K4 = 4000K — same CCT choice on all five heights.
- **Supply & build:** 100–240V direct mains · non-dimmable · die-cast AL + PC in Sand Black or Sand Gray.
- **Siting:** keep short heads below bedroom-window sightlines; aim pools across the walk so glare stays off pedestrians.
- **Family guidance:** square park columns for lawns and estate drives see CUBO-G · slim architectural line see LAN.

Scan for live datasheet