OUTDOOR LUMINAIRES — BOLLARD

VOID Glare-Free LED Path Bollard

VOID-SS 7W glare-free flood · 108×108 head | COB | 2700K / 4000K | Ra80

HEIGHTS 300 / 400 / 600 / 800 / 1000 MM · DIE-CAST AL + PC · 100–240V




KEY FACTS

VOID is a glare-free path bollard that lights the paving, not the eyes. Its 7W COB head sits recessed behind an internal flange in a 108×108mm square body — five heights from 30 to 100cm in Black or Grey at 2700K/4000K Ra80.

POWER	7W · single family
HEIGHTS	300–1000 mm · 5 models
LIGHT	COB · 2700K/4000K · Ra80
BODY	AL + PC · 100–240V · Non-dim
FINISH	Black Grey

Poolside decks · Courtyards · Pool edges · Walkways · Pathways

ORDERING — VOID GLARE-FREE FLOOD · 7W



PRODUCT	DIMENSION	CRI	CCT	POWER
451030 12K3/K4	108*108*300MM	Ra80	2700K/4000K	7W
451040 12K3/K4	108*108*400MM	Ra80	2700K/4000K	7W
451060 12K3/K4	108*108*600MM	Ra80	2700K/4000K	7W
451080 12K3/K4	108*108*800MM	Ra80	2700K/4000K	7W
4510100 12K3/K4	108*108*1000MM	Ra80	2700K/4000K	7W



APPLICATION

- **Flood first:** VOID washes the deck for safe footing — for accent spot on trees or signs see BAM.
- **Height rule:** 30–40 cm edges flower beds and deck rims · 60 cm marks paths · 80–100 cm flags entries.
- **Spacing rule:** 3–4 m apart with flood pools just overlapping; tighten at bends and steps.
- **CCT rule:** 2700K calms evening decks · 4000K suits working courtyards and walkway edges.

NOTES

- **Ordering suffix:** K3 = 2700K · K4 = 4000K — one CCT per project across all five heights.
- **Supply & build:** 100–240V direct mains · non-dimmable · die-cast AL + PC in Black or Grey.
- **Placing:** keep low 30–40 cm bodies at the pool edge below standing eye lines; mark step nosings.
- **Family guidance:** for heavy-duty driveways see SEMI · for accent spot see BAM.

Scan for live datasheet